

High Torque Nutrunners



With the Atlas Copco LMP/LTP61 range of twin-motor pistol grip nutrunners you get the highest possible torque and speed in relation to the weight of the tool. Fast, accurate and highly user-friendly, the tools are available in reversible versions for maximum flexibility.

High torque *nutrunners*



LMP61 H900-25

The twin motors in the **LMP61** pistol grip nutrunner gives extremely fast rundown and high accuracy with minimum air consumption. The torque level on **LMP** models depends on the pressure of the air fed to the tool – higher pressure creates higher torque. A swiveling function makes tool positioning easy and they are available in reversible and non-reversible versions.

| Model | Bolt size mm | Square drive in | Max torque at 6.3 bar Nm | Min torque at 3 bar Nm | Free speed r/min | Weight ^a kg | Length mm | Air consumption at free speed l/s | Recommended hose size mm | Air inlet thread BSP | Spline type | Ordering No. |
|-----------------------|--------------|-----------------|--------------------------|------------------------|------------------|------------------------|-----------|-----------------------------------|--------------------------|----------------------|-------------|--------------|
| Non-reversible | | | | | | | | | | | | |
| LMP24 H005-10 | M8 | 3/8" | 30 | 14 | 500 | 1.0 | 210 | 11 | 10 | 1/4" | 1 | 8431 0245 49 |
| LMP24 H003-13 | M8 | 1/2" | 40 | 14 | 330 | 1.2 | 210 | 11 | 10 | 1/4" | 1 | 8431 0245 64 |
| LMP24 H002-13 | M10 | 1/2" | 58 | 27 | 240 | 1.3 | 230 | 11 | 10 | 1/4" | 2 | 8431 0245 31 |
| LMP61 H230-19 | M16 | 3/4" | 230 | 130 | 1000 | 3.0 | 223 | 20 | 13 | 3/8" | 3 | 8431 0803 19 |
| LMP61 H350-20 | M18 | 3/4" | 350 | 200 | 650 | 3.9 | 260 | 20 | 13 | 3/8" | 4 | 8431 0803 26 |
| LMP61 H500-20 | M20 | 3/4" | 500 | 300 | 450 | 3.9 | 260 | 20 | 13 | 3/8" | 4 | 8431 0803 33 |
| LMP61 H900-25 | M24 | 1" | 900 | 500 | 260 | 4.5 | 282 | 20 | 13 | 3/8" | 5 | 8431 0803 47 |
| Reversible | | | | | | | | | | | | |
| LMP24 HR003-13 | M8 | 1/2" | 30 | 14 | 250 | 1.2 | 210 | 11 | 10 | 1/4" | 1 | 8431 0245 91 |
| LMP24 HR002-13 | M10 | 1/2" | 40 | 20 | 180 | 1.3 | 230 | 11 | 10 | 1/4" | 2 | 8431 0245 70 |
| LMP61 HR170-13 | M14 | 1/2" | 170 | 100 | 1400 | 3.0 | 238 | 20 | 13 | 3/8" | 3 | 8431 0804 11 |
| LMP61 HR230-19 | M16 | 3/4" | 230 | 130 | 1000 | 3.0 | 275 | 20 | 13 | 3/8" | 3 | 8431 0804 18 |
| LMP61 HR350-20 | M18 | 3/4" | 350 | 200 | 650 | 3.9 | 275 | 20 | 13 | 3/8" | 4 | 8431 0804 25 |
| LMP61 HR500-20 | M20 | 3/4" | 500 | 300 | 450 | 3.9 | 320 | 21 | 13 | 3/8" | 4 | 8431 0804 32 |
| LMP61 HR700-25 | M22 | 1" | 700 | 400 | 350 | 4.5 | 305 | 20 | 13 | 3/8" | 5 | 8431 0804 39 |
| LMP61 HR900-25 | M24 | 1" | 900 | 500 | 260 | 4.5 | 305 | 20 | 13 | 3/8" | 5 | 8431 0804 46 |
| LMP61 HR1500-25 | M30 | 1" | 1600 | 900 | 140 | 6.8 | 345 | 20 | 13 | 3/8" | 9 | 8431 0804 53 |

^a Weight excluding reaction bar.

Accessories Included

| FOR LMP24 | FOR LMP61/LTP61 | FOR LTP61 HR1900/2800/3800 |
|-----------------|------------------|----------------------------|
| Suspension yoke | Suspension yoke | Suspension yoke |
| Reaction bar | Protective cover | Protective cover |
| | | Reaction bar |



LTP61 HR900-25-MT

LTP61 pistol grip nutrunners are equipped with twin motors and a shut-off valve that ensures that the tool shuts down when the preset torque level is reached.

The torque-to-weight ratio is extremely high, and the tool is reversible. On the LTP61 HR900-25-MT a Multi Torque Selector makes it possible to preset up to four different shut-off levels. This is an efficient solution where various assembly operations take place, multistage tightening operations are required, or many torque settings are needed.

| Model | Bolt size mm | Square drive in | Max torque at 6.3 bar Nm | Min torque at 3 bar Nm | Free speed r/min | Weight ^a kg | Length mm | Air consumption at free speed l/s | Recommended hose size mm | Air inlet thread BSP | Spline type | Ordering No. |
|---|--------------|-----------------|--------------------------|------------------------|------------------|------------------------|-----------|-----------------------------------|--------------------------|----------------------|-------------|--------------|
| Non reversible | | | | | | | | | | | | |
| LTP61 H100-13 | M12 | 1/2" | 55-100 | 45 | 1800 | 3.0 | 223 | 20 | 13 | 3/8" | 3 | 8431 0800 07 |
| LTP61 H170-13 | M14 | 1/2" | 95-170 | 70 | 1100 | 3.0 | 223 | 20 | 13 | 3/8" | 3 | 8431 0800 14 |
| LTP61 H230-19 | M16 | 3/4" | 125-230 | 85 | 820 | 3.0 | 223 | 20 | 13 | 3/8" | 3 | 8431 0800 21 |
| LTP61 H350-20 | M18 | 3/4" | 190-350 | 145 | 520 | 3.9 | 260 | 20 | 13 | 3/8" | 4 | 8431 0800 28 |
| LTP61 H500-20 | M20 | 3/4" | 275-500 | 220 | 360 | 3.9 | 260 | 20 | 13 | 3/8" | 4 | 8431 0800 35 |
| LTP61 H700-25 | M22 | 1" | 360-650 | 280 | 280 | 4.5 | 305 | 20 | 13 | 3/8" | 5 | 8431 0800 42 |
| LTP61 H900-25 | M24 | 1" | 480-870 | 300 | 210 | 4.5 | 282 | 20 | 13 | 3/8" | 5 | 8431 0800 49 |
| LTP61 H1500-25 | M30 | 1" | 850-1500 | 700 | 115 | 6.8 | 323 | 20 | 13 | 3/8" | 9 | 8431 0800 56 |
| Reversible | | | | | | | | | | | | |
| LTP61 HR100-13 | M12 | 1/2" | 55-100 | 45 | 1800 | 3.0 | 235 | 20 | 13 | 3/8" | 3 | 8431 0801 08 |
| LTP61 HR170-13 | M14 | 1/2" | 95-170 | 70 | 1100 | 3.0 | 238 | 20 | 13 | 3/8" | 3 | 8431 0801 15 |
| LTP61 HR230-19 | M16 | 3/4" | 125-230 | 85 | 820 | 3.0 | 275 | 20 | 13 | 3/8" | 3 | 8431 0801 22 |
| LTP61 HR350-20 | M18 | 3/4" | 190-350 | 145 | 520 | 3.9 | 275 | 20 | 13 | 3/8" | 4 | 8431 0801 29 |
| LTP61 HR500-20 | M20 | 3/4" | 275-500 | 220 | 360 | 3.9 | 275 | 20 | 13 | 3/8" | 4 | 8431 0801 36 |
| LTP61 HR700-25 | M22 | 1" | 360-650 | 280 | 280 | 4.5 | 305 | 20 | 13 | 3/8" | 5 | 8431 0801 43 |
| LTP61 HR900-25 | M24 | 1" | 480-870 | 300 | 210 | 4.5 | 305 | 20 | 13 | 3/8" | 5 | 8431 0801 50 |
| LTP61 HR1500-25 | M30 | 1" | 850-1500 | 700 | 115 | 6.8 | 345 | 20 | 13 | 3/8" | 9 | 8431 0801 57 |
| LTP61 HR1900-38 | M30 | 1 1/2" | 1050-1900 | 800 | 90 | 14.1 | 380 | 20 | 13 | 3/8" | 8 | 8431 0801 64 |
| LTP61 HR2800-38 | M36 | 1 1/2" | 1550-2800 | 1200 | 65 | 14.1 | 380 | 20 | 13 | 3/8" | 8 | 8431 0801 71 |
| LTP61 HR3800-38 | M42 | 1 1/2" | 2100-3800 | 1600 | 50 | 14.1 | 380 | 20 | 13 | 3/8" | 8 | 8431 0801 78 |
| Prevailing applications | | | | | | | | | | | | |
| Non reversible | | | | | | | | | | | | |
| LTP61 PH100-13 | M12 | 1/2" | 60-110 | 45 | 700 | 3.0 | 223 | 20 | 13 | 3/8" | 3 | 8431 0807 04 |
| LTP61 PH170-13 | M14 | 1/2" | 100-180 | 70 | 440 | 3.0 | 223 | 20 | 13 | 3/8" | 3 | 8431 0807 12 |
| LTP61 PH230-19 | M16 | 3/4" | 130-240 | 90 | 320 | 3.0 | 223 | 20 | 13 | 3/8" | 3 | 8431 0807 17 |
| LTP61 PH350-20 | M18 | 3/4" | 210-370 | 150 | 200 | 3.9 | 260 | 20 | 13 | 3/8" | 4 | 8431 0807 24 |
| LTP61 PH500-20 | M20 | 3/4" | 300-520 | 200 | 140 | 3.9 | 260 | 20 | 13 | 3/8" | 4 | 8431 0807 31 |
| LTP61 PH700-25 | M22 | 1" | 400-680 | 280 | 100 | 4.5 | 305 | 20 | 13 | 3/8" | 5 | 8431 0807 38 |
| LTP61 PH900-25 | M24 | 1" | 500-900 | 350 | 80 | 4.5 | 282 | 20 | 13 | 3/8" | 5 | 8431 0807 41 |
| Prevailing applications - reversible | | | | | | | | | | | | |
| LTP61 PHR1500-25 | M30 | 1" | 900-1600 | 650 | 45 | 6.8 | 345 | 20 | 13 | 3/8" | 9 | 8431 0807 68 |
| Multi torque selector | | | | | | | | | | | | |
| LTP61 HR500-20-MT | M20 | 3/4" | 275-500 | 220 | 360 | 4.2 | 325 | 20 | 13 | 3/8" | 4 | 8431 0806 30 |
| LTP61 HR700-25-MT | M22 | 1" | 360-650 | 280 | 280 | 4.8 | 355 | 20 | 13 | 3/8" | 5 | 8431 0806 33 |
| LTP61 HR900-25-MT | M24 | 1" | 480-870 | 300 | 210 | 4.8 | 355 | 20 | 13 | 3/8" | 5 | 8431 0806 37 |
| LTP61 HR1500-25-MT | M30 | 1" | 850-1500 | 700 | 115 | 7.1 | 395 | 20 | 13 | 3/8" | 9 | 8431 0806 44 |

^a Weight excluding reaction bar.

Productivity Kits

| Model | Economical flow | Max air flow | Hose, 5 m | Coupling | Lubrication | Ordering No. |
|---|-----------------|--------------|---------------|------------|-------------|--------------|
| For small nutrunners with 3/8" BSP air inlet | | | | | | |
| MIDI Optimizer F/RD EQ08-C10 | 13 l/s | 16 l/s | Cablair 10 mm | ErgoQIC 08 | Yes | 8202 0850 07 |
| For small nutrunners with 1/4" BSP air inlet | | | | | | |
| MIDI Optimizer F/RD EQ08-C10 | 13 l/s | 16 l/s | Cablair 10 mm | ErgoQIC 08 | Yes | 8202 0850 03 |
| MIDI Optimizer F/RD EQ10-R10 | 13 l/s | 16 l/s | Rubair 10 mm | ErgoQIC 10 | Yes | 8202 0850 16 |
| For nutrunners with 3/8" BSP air inlet | | | | | | |
| MIDI Optimizer F/RD EQ10-C13 | 21 l/s | 23 l/s | Cablair 13 mm | ErgoQIC 10 | Yes | 8202 0850 02 |
| For nutrunners with 1/4" BSP air inlet | | | | | | |
| MIDI Optimizer F/RD EQ10-C13-1/4 | 27 l/s | 23 l/s | Cablair 13 mm | ErgoQIC 10 | Yes | 8202 0850 11 |
| For nutrunners with 3/8" BSP air inlet | | | | | | |
| MIDI Optimizer F/RD EQ10-T13 | 21 l/s | 35 l/s | Turbo 13 mm | ErgoQIC 10 | Yes | 8202 0850 17 |
| For nutrunners with 1/2" BSP air inlet | | | | | | |
| MIDI Optimizer F/R EQ10-T13 | 21 l/s | 35 l/s | Turbo 13 mm | ErgoQIC 10 | No | 8202 0850 04 |
| MIDI Optimizer F/RD EQ10-T13 | 21 l/s | 35 l/s | Turbo 13 mm | ErgoQIC 10 | Yes | 8202 0850 13 |

Accessories

For LMP24

| Model | Ordering No. |
|------------------------|--------------|
| Hose nipple | 9000 0247 00 |
| Swivel attachment | 4210 2249 80 |
| Exhaust hose | 4210 2053 00 |
| Support handle | 4110 1355 82 |
| (for H/HR002 only) | |
| Spindle extension | |
| 115 mm x 1/2" | 4210 2154 80 |
| (for H/HR002 only) | |
| 50 mm x 3/8" | 4210 2158 80 |
| (for H/HR011/005 only) | |
| 1/4" hex bit holder | 4021 0443 00 |
| (for H/HR011/005 only) | |
| 1/2" square adapter | 4210 2157 80 |
| (for H/HR011/005 only) | |

For LMP/LTP61

| Model | Ordering No. |
|--|--------------|
| Hose nipple | 9000 0242 00 |
| Exhaust hose | 4210 2201 00 |
| Protective cover | |
| Standard LTP61 | 4210 4672 00 |
| LTP 61 with MT unit | 4210 4672 01 |
| Multi torque selector LTP61 | 4210 4636 95 |
| Quick change retainer | |
| – 1/2" square models | 4250 1190 00 |
| – 3/4" square models | 4210 3476 80 |
| – 1" square models | 4210 3524 80 |
| Shut-off override for LTP61 | 4210 3545 80 |
| Swivelling type MultiFlex connector 3/8" (BSP) | 8202 1350 22 |
| Swivelling type MultiFlex connector 3/8" (NPT) | 8202 1350 28 |

Swivelling suspension yoke LMP/LTP61

| Model | Ordering No. |
|-------------------------------|--------------|
| Mounting dia Ø 54 mm | |
| PH/H 100-13 | 4210 3088 80 |
| PH/H 170-13 | |
| PH/H 230-19 | |
| PH/H 350-20 | |
| PH/H 500-20 | |
| PH/H 700-25 | |
| PH/H 900-25 | |
| Mounting dia Ø 60 mm | |
| HR 100-13 | 4210 3088 84 |
| HR 170-13 | |
| HR 230-19 | |
| Mounting dia Ø 63.5 mm | |
| H 1900-38 | 4210 3088 83 |
| H 2800-38 | |
| H 3800-38 | |
| Mounting dia Ø 67 mm | |
| HR 350-20 | 4210 3088 82 |
| HR 500-20 | |
| PHR/HR 700-25 | |
| PHR/HR 900-25 | |
| HR 1900-38 | 4210 3088 85 |
| HR 2800-38 | |
| HR 3800-38 | |
| Mounting dia Ø 83.5 | |
| PH/H 1500-25 | 4210 3088 81 |
| PHR/HR 1500-25 | |

Reaction bars LMP/LTP61

| Spline dia mm | Square drive size mm/in | CC distance mm | Ordering No. |
|--|-------------------------|----------------|--------------|
| Steel bar | | | |
| Spline 1 | 268/36/18 | | 4210 1798 01 |
| Spline 2 | 270/35/10 | | 4220 1903 00 |
| Spline 3 | 400/56/12 | | 4210 2219 80 |
| Spline 4 | 500/62/15 | | 4210 2183 80 |
| Spline 5 | 500/62/15 | | 4210 2726 80 |
| Spline 6 | 560/80/15 | | 4220 1200 01 |
| Spline 8 | 500/150/20 | | 4210 3899 03 |
| Spline 9 | 500/85/20 | | 4210 3899 80 |
| Square steel bracket | | | |
| Spline 3 | 100/50/12 | | 4210 2219 03 |
| Spline 4 | 125/65/16 | | 4210 2183 01 |
| Spline 5 | 125/65/16 | | 4210 2726 01 |
| Spline 6 | 200/100/15 | | 4220 1200 00 |
| Spline 7 | 250/150/20 | | 4220 1445 00 |
| Spline 8 | 250/160/20 | | 4220 1972 91 |
| Spline 9 | 150/85/20 | | 4210 3899 01 |
| Triangular steel bracket | | | |
| Spline 2 | 73/72/14 | | 4220 2137 02 |
| Spline 3 | 82/80/15 | | 4220 2137 03 |
| Spline 6 | 112/109/15 | | 4220 2137 06 |
| Spline 6 | 150/145/20 | | 4220 2137 16 |
| Sliding drive reaction bar | | | |
| Spline 3 | 1/2 | 70-120 | 4210 4481 83 |
| Spline 3 | 3/4 | 70-120 | 4210 4481 63 |
| Spline 3 | 1/2 | 82-218 | 4210 4616 83 |
| Spline 3 | 3/4 | 82-218 | 4210 4616 63 |
| Spline 4 | 3/4 | 76-126 | 4210 4481 84 |
| Spline 4 | 3/4 | 82-218 | 4210 4616 84 |
| Spline 5 | 1 | 80-125 | 4210 4481 85 |
| Spline 5 | 1 | 82-218 | 4210 4616 85 |
| Spline 9 | 1 | 80-130 | 4210 4481 89 |
| Spline 9 | 1 | 80-280 | 4210 4616 89 |
| S-Type reaction bar | | | |
| Spline 3 | 110/18/12 | | 4210 4480 03 |
| Spline 4 | 120/22/15 | | 4210 4480 04 |
| Spline 5 | 130/25/15 | | 4210 4480 05 |
| Spline 6 | 125/25/15 | | 4210 4480 06 |
| Spline 8 | 200/65/20 | | 4210 4480 08 |
| Spline 9 | 160/40/20 | | 4210 4480 09 |
| L-Type aluminum bar | | | |
| Spline 3 | 266x300/29/15 | | 4210 2219 08 |
| Spline 4 | 144x150/42/15 | | 4210 2183 08 |
| Straight aluminum bar | | | |
| Spline 3 | L = 400 | | 4210 2219 01 |
| Extended sliding drive reaction bar | | | |
| Spline 5 | 1 | 68-112 | 4210 4498 80 |
| Extended sliding tube reaction bar | | | |
| Spline 5 | 1 | 68-112 | 4210 4498 82 |
| Bracket stepped | | | |
| Spline 1 | 70/36/13 | | 4210 1798 02 |
| Spline 2 | 70/41/14 | | 4210 2134 02 |

Service Kits

| Model | Trigger kit | General service kit |
|-----------|--------------|---------------------|
| LMP24 | 4210 1934 91 | 4081 0105 90 |
| LMP/LTP61 | 4210 2190 91 | 4081 0397 90 |

RTP

pneumatic nutrunners



The light weight of the **RTP NUTRUNNER** will surprise you, yet its high speed motor has the power you need to tighten big bolts. A robust, lightweight reaction bar absorbs the torque. Noise and vibration levels are lower than in traditional impact wrenches.

Among the smallest on the market, the RTP's slim gearpack gives you effortless access to bolts in cramped spaces. Tightening accuracy and repeatability are high.

Plug & play! Simply connect the RTP to your air line and start working with it. The torque output of the RTP is adjusted with an Atlas Copco FRL air pressure unit, helping to prolong the lifetime and torque accuracy of the tool. The tool's exchangeable drive simplifies maintenance and cuts repair costs.

RTP nutrunner Kit

| Model | Bolt size mm | Square drive in | Min torque at 1,5 bar Nm | Max torque at 6.3 bar Nm | Free speed r/min | Weight ^a kg | Length mm | CS distance mm | Air consumption at free speed l/s | Rec. hose size mm | Air inlet thread in | Ordering No. |
|---------------|--------------|-----------------|--------------------------|--------------------------|------------------|------------------------|-----------|----------------|-----------------------------------|-------------------|---------------------|--------------|
| RTP1300-HR20 | 20-27 | 3/4 | 320 | 1300 | 20 | 3.7 | 248 | 32 | 23 | 13 | 3/8 | 8431 1013 10 |
| RTP2600-HR25 | 20-36 | 1 | 700 | 2600 | 10 | 5 | 300 | 34 | 23 | 13 | 3/8 | 8431 1026 10 |
| RTP4100-HR25 | 30-45 | 1 | 1000 | 4100 | 10 | 8.7 | 335 | 41 | 31 | 13 | 3/8 | 8431 1040 10 |
| RTP8100-GIR38 | 33-52 | 1 1/2 | 2200 | 8100 | 10 | 13.5 | 444 | 51 | 50 | 13 | 1/2 | 8431 1081 10 |

^aWeight excluding reaction bar.

NOTE: For all models in the table declared noise and vibration emissions according to ISO 28927-2 and ISO 15744. Sound pressure level for RTP1300 HR20 is 90 dB(A), RTP2600-HR25 90 dB(A), RTP4100-HR25 90 dB(A), RTP8100-GIR38 99 dB(A) and vibration value for all models are <2.5 m/s².

Accessories Included

| Model | Description | Ordering No. |
|-----------------------|--|--------------|
| RTP1300 | Reaction bar, S-type | 4210 4480 90 |
| RTP2600 | Reaction bar, S-type | 4210 4480 94 |
| RTP4100 | Reaction bar, S-type | 4210 4480 93 |
| RTP8100 | Reaction bar, S-type | 4210 4480 92 |
| RTP1300 / 2600 / 4100 | Nipple, ErgoNIP 10. M10, BSP | 8202 1220 19 |
| RTP8100 | Nipple, ErgoNIP 10. M15, BSP | 8002 1220 27 |
| RTP1300 / 2600 / 4100 | Productivity kit FRL stand, BSP ^o | 9090 3030 02 |
| RTP8100 | Productivity kit FRL stand, BSP ^o | 9090 3030 04 |

^o Hose included



Optional Accessories

| Model | Description | Ordering No. |
|-----------------------|------------------------------|--------------|
| RTP1300 / 2600 / 4100 | MultiFlex swivel 3/8 BSP | 8202 1350 22 |
| RTP8100 | MultiFlex swivel 1/2 BSP | 8202 1350 24 |
| RTP1300 / 2600 / 4100 | Trigger guard | 4210 4759 90 |
| RTP1300 | Suspension yoke | 4210 3088 83 |
| RTP2600 | Suspension yoke | 4210 3088 82 |
| RTP4100 | Suspension yoke | 4210 3088 81 |
| RTP8100 | Suspension yoke | 4210 4780 90 |
| RTP1300 | Reaction bar, sliding-drive | 4210 4752 90 |
| RTP1300 | Reaction bar, steel bar | 4210 4757 90 |
| RTP1300 | Reaction bar, square bracket | 4210 4758 90 |
| RTP2600 | Reaction bar, sliding-drive | 4210 4752 93 |
| RTP2600 | Reaction bar, steel bar | 4210 4757 93 |
| RTP2600 | Reaction bar, square bracket | 4210 4758 93 |
| RTP4100 | Reaction bar, sliding-drive | 4210 4752 91 |
| RTP4100 | Reaction bar, steel bar | 4210 4757 91 |
| RTP4100 | Reaction bar, square bracket | 4210 4758 91 |
| RTP8100 | Reaction bar, sliding-drive | 4210 4752 92 |
| RTP8100 | Reaction bar, steel bar | 4210 4757 92 |
| RTP8100 | Reaction bar, square bracket | 4210 4758 92 |

NOTE: All reaction bars includes a snap ring



Service Kits

| Model | Description | Ordering No. |
|---------|-----------------|--------------|
| RTP1300 | Small parts kit | 4082 0125 90 |
| RTP2600 | Small parts kit | 4082 0148 90 |
| RTP4100 | Small parts kit | 4082 0116 91 |
| RTP8100 | Small parts kit | 4082 0126 90 |
| RTP1300 | Service kit | 4081 0510 90 |
| RTP2600 | Service kit | 4081 0510 90 |
| RTP4100 | Service kit | 4081 0504 90 |
| RTP8100 | Service kit | 4081 0511 90 |

