


POWERDYNE IMPACT WRENCHES are rugged and powerful suitable for a wide range of mechanical applications: automotive service and repair work, farm workshops, motorcycle repairs, lawnmower repairs, electrical & mechanical equipment repairs and manufacturing.

Quickly and efficiently take on a broad range of automotive applications from small fastener work to heavy duty use on truck, agricultural and off-road equipment service.


3/8" Impact Wrench – Jumbo Hammer 53-AIW-38R



SQUARE DRIVE	3/8"
BOLT CAPACITY	3/8"
SPEED	10,000 RPM
WORKING TORQUE RANGE	25 – 200 Nm
MAXIMUM TORQUE	240 Nm
OPERATING AIR PRESSURE	90 PSI
AV. AIR CONSUMPTION	3.5 CFM
RECOMMENDED HOSE SIZE	3/8"
AIR INLET SIZE	1/4"
TOOL WEIGHT	1.35 KG
OVERALL LENGTH	152 mm
ORDER NUMBER	53-AIW-38R



3/4" Impact Wrench – Twin Hammer 53-IAW-6R



SQUARE DRIVE	3/4"
BOLT CAPACITY	3/4"
FREE SPEED	6,500 RPM
MAX TORQUE	1016 Nm
OPERATING AIR PRESSURE	90 PSI
AV. AIR CONSUMPTION	5 CFM
RECOMMENDED HOSE SIZE	3/8"
AIR INLET SIZE	1/4"
WEIGHT	4.6 KG
LENGTH	235 mm
ORDER NUMBER	53-IAW-6R



PLEASE NOTE: Impact wrenches must use HIGH FLOW fittings or the tools will not achieve the stated maximum torque.

1/2" Impact Wrench – Twin Hammer

53-IAW-4R


SQUARE DRIVE	1/2"
BOLT CAPACITY	3/8"
SPEED	7,000 RPM
MAXIMUM TORQUE	550 Nm
WORKING TORQUE RANGE	25 – 250 Nm
OPERATING AIR PRESSURE	90 PSI
AV. AIR CONSUMPTION	3.5 CFM
RECOMMENDED HOSE SIZE	3/8"
AIR INLET SIZE	1/4"
WEIGHT	3 KG
LENGTH	180 mm
ORDER NUMBER	53-IAW-4R



1/2" Impact Wrench – Twin Hammer

53-NAIW-12F

SQUARE DRIVE	1/2"
BOLT CAPACITY	5/8"
FREE SPEED	7,500 RPM
MAX TORQUE	542 Nm
OPERATING AIR PRESSURE	90 PSI
AV. AIR CONSUMPTION	4.2 CFM
RECOMMENDED HOSE SIZE	3/8"
AIR INLET SIZE	1/4"
WEIGHT	2.6 KG
LENGTH	180 mm
ORDER NUMBER	53-NAIW-12F



TWIN HAMMER

Unique mechanism for continuous torque increase with two solid ring hammers.

It delivers an instantaneous, balanced blow.

More powerful than any other mechanism on the market.

JUMBO HAMMER

Same mechanism as Twin Hammer but with one hammer only.

It delivers an instantaneous, balanced blow, with excellent impacting power.

PIN CLUTCH (DYNA PACT CLUTCH)

Two Pin Clutch hammers strike the anvil, provides high torque, low vibration and fast run downs. This mechanism delivers higher performance and extended durability.

The Powerdyne range of **3/8" Impact Wrenches** are ideal for a wide range of mechanical applications: Automotive servicing, auto-body work, farm workshops, motorcycle repairs, lawnmower repairs, electrical and mechanical equipment repairs and manufacturing.

3/8" Impact Wrench

53-AIW-380SP

SQUARE DRIVE	3/8"
BOLT CAPACITY	3/8"
SPEED	10,000 RPM
WORKING TORQUE RANGE	
MAXIMUM TORQUE	100 Nm
OPERATING AIR PRESSURE	90 PSI
AV. AIR CONSUMPTION	4 CFM
RECOMMENDED HOSE SIZE	1/4"
AIR INLET SIZE	3/8"
TOOL WEIGHT	1.15 KG
OVERALL LENGTH	180 mm
ORDER NUMBER	53-AIW-380SP



3/4" Butterfly Impact Wrench

53-AIW-3B

SQUARE DRIVE	3/8"
BOLT CAPACITY	3/8"
FREE SPEED	10,000 RPM
MAX TORQUE	102 Nm
OPERATING AIR PRESSURE	90 PSI
AV. AIR CONSUMPTION	3 CFM
RECOMMENDED HOSE SIZE	3/8"
AIR INLET SIZE	1/4"
WEIGHT	1 KG
LENGTH	140 mm
ORDER NUMBER	53-AIW-3B

