

POWERDYNE Pistol Grip Drills are manufactured with a heavy duty gearbox for hi-torque drilling power and balancing the load on the gears and bearings for longer tool life. These tools have heavy-duty ball bearing and needle bearing construction. They also have a rear exhaust, which directs air away from the work area.

The 3/8" pistol grip drills are fitted with a keyless Jacobs chuck, silencers and cushioned handles; industrial keyed chucks are also available as an added option.

3/8" NON-REVERSIBLE DRILL

53-AD-389

CAPACITY	3/8" (10 mm)
FREE SPEED	2500 RPM
SPINDLE THREAD	3/8" – 24
OPERATING AIR PRESSURE	90 PSI
AV. AIR CONSUMPTION	4 CFM
RECOMMENDED HOSE SIZE	3/8"
AIR INLET SIZE	1/4"
TOOL WEIGHT	1 KG
OVERALL LENGTH	170 mm
CHUCK TYPE	KEYLESS
ORDER NUMBER	53-AD-389
KEYLESS CHUCKS (INCLUDED)	53-AAAD-38K
KEYED CHUCK (OPTIONAL)	53-AAAD-38
EXHAUST SOUND REDUCING HOSE	53-AT-400GH



Fitted with Jacobs KEYED Chuck

3/8" NON-REVERSIBLE DRILL

53-AD-389KL

CAPACITY	3/8" (10 mm)
FREE SPEED	2500 RPM
SPINDLE THREAD	3/8" – 24
OPERATING AIR PRESSURE	90 PSI
AV. AIR CONSUMPTION	4 CFM
RECOMMENDED HOSE SIZE	3/8"
AIR INLET SIZE	1/4"
TOOL WEIGHT	1 KG
OVERALL LENGTH	170 mm
CHUCK TYPE	KEYLESS
ORDER NUMBER	53-AD-389KL



3/8" REVERSIBLE DRILL

53-AD-380RCKL

The 3/8" pistol grip drills are fitted with a keyless Jacobs chuck, silencers and cushioned handles; industrial keyed chucks are also available as an added option. Compact and lightweight these tools are ideal for light service and auto-body shop work, frame drilling, accessory installation and riveting, trim work, wire brushing and light sanding.



CAPACITY	3/8" (10 mm)
FREE SPEED	1800 RPM
SPINDLE THREAD	3/8" – 24
OPERATING AIR PRESSURE	90 PSI
AV. AIR CONSUMPTION	4 CFM
RECOMMENDED HOSE SIZE	3/8"
AIR INLET SIZE	1/4"
TOOL WEIGHT	1.15 KG
OVERALL LENGTH	170 mm
CHUCK TYPE	KEYLESS
ORDER NUMBER	53-AD-380RCKL
KEYLESS CHUCKS (INCLUDED)	53-AAAD-38K
KEYED CHUCK (OPTIONAL)	53-AAAD-38
EXHAUST SOUND REDUCING HOSE	53-AT-400GH



**Optional Jacobs KEYED Chuck
Part No. 53-AAAD-38**

1/2" NON-REVERSIBLE DRILL

53-AD-120

- Alloy steel precision, double reduction planetary gear system provides a lower free speed for the extra power needed for heavy drilling.
- Auxiliary side handle for convenient handling during intensive drilling.
- Drills are fitted with a Jacobs Chuck,
- Rear muffled handled exhaust keeps sound low.
- Cushioned handle for comfort and precision.

CAPACITY	1/2"
FREE SPEED	500 RPM
SPINDLE THREAD	3/8" – 24 TPI
OPERATING AIR PRESSURE	90 PSI
AV. AIR CONSUMPTION	4 CFM
RECOMMENDED HOSE SIZE	3/8"
AIR INLET SIZE	1/4"
TOOL WEIGHT	1.8 KG
OVERALL LENGTH	221 mm
CHUCK TYPE	KEYED
ORDER NUMBER	53-AD-120



1/2" REVERSIBLE DRILL

53-AD-120RC

CAPACITY	1/2"
FREE SPEED	500 RPM
SPINDLE THREAD	3/8" – 24 TPI
OPERATING AIR PRESSURE	90 PSI
AV. AIR CONSUMPTION	4 CFM
RECOMMENDED HOSE SIZE	3/8"
AIR INLET SIZE	1/4"
TOOL WEIGHT	1.8 KG
OVERALL LENGTH	221 mm
CHUCK TYPE	KEYED
ORDER NUMBER	53-AD-120

