

**POWERDYNE Sanders & Polishers** are perfect for any D.I.Y projects you might be undertaking. When you need consistent high-performance with minimum vibration on weld smoothing, rust removal, rough shape filler, blending and smoothing filler, final filler feather-edging, body filler removal, erasing and general grinding, turn to one of our finishing tools to take care of business.

## DUAL ACTION SANDER (150mm)

### 53-AT-200JSF

SANDING PAD SIZE	150 mm
MAX FREE SPEED	10,000 RPM
ORBITAL STROKE	4.8 mm
SPINDLE SIZE	5/16" – 24 UNF
OPERATING AIR PRESSURE	90 PSI
AV. AIR CONSUMPTION	5 CFM
RECOMMENDED HOSE SIZE	3/8" (10 mm)
AIR INLET SIZE	1/4" BSP
WEIGHT	2 KG
ORDER NO.	<b>53-AT-200JSF</b>
SANDING PAD (REPLACEMENT)	<b>53-AADA-6F</b>



## RANDOM ORBITAL SANDER

### 53-IADA-6M

Industrial quality finishing sander, equipped with built-in silencer, no vacuum system.

SANDING PAD SIZE	150 mm
MAX FREE SPEED	10,000 RPM
ORBITAL STROKE	4.8 mm
SPINDLE SIZE	5/16" – 24 UNF
OPERATING AIR PRESSURE	90 PSI
AV. AIR CONSUMPTION	5 CFM
RECOMMENDED HOSE SIZE	3/8" (10 mm)
AIR INLET SIZE	1/4" BSP
WEIGHT	1.24 KG
SANDER ORDER NO.	<b>53-IADA-6M</b>
SANDING PAD (VELCRO)	<b>53-AADA-6FV</b>
SANDING PAD (STICK ON)	<b>53-AADA-6F</b>
SANDING PAD (VAC WITH HOLES)	<b>53-AADA-6FVH</b>



## ORBITAL AIR SANDER

53-AT-300J

SANDING PAD SIZE	90 x 170 mm
ABRASIVE PAPER SIZE	90 x 228 mm
MAX FREE SPEED	8,000 RPM
ORBITAL STROKE	4.8 mm
OPERATING AIR PRESSURE	90 PSI
AV. AIR CONSUMPTION	6 CFM
RECOMMENDED HOSE SIZE	3/8" ID
AIR INLET SIZE	1/4"
WEIGHT	1.95 KG
ORDER NO.	<b>53-AT-300J</b>
SANDING PAD (REPLACEMENT)	<b>53-AAJS-1</b>



## BELT SANDERS

	AT-10BS SANDER	0.7 HP SANDER
SANDING BELT SIZE	10 x 330 mm	10 x 540 mm
FREE SPEED	16,000 RPM	
OPERATING AIR PRESSURE	90 PSI	90 PSI
AIR CONSUMPTION	14.2 CFM	
RECOMMENDED HOSE SIZE	3/8" ID	3/8" ID
AIR INLET SIZE	1/4" BSP	1/4" BSP
LENGTH	290 mm	460 mm
WEIGHT	0.76 KG	2.15 KG
ORDER NO.	<b>53-AT-10BS</b>	<b>53-ABS-730</b>



## HIGH SPEED PISTOL GRIP SANDER

53-AT-600US

Fitted with mesh inlet filter and speed adjustment valve. Suitable for use with surface conditioning pads. Includes 3 fibre backing discs.

<b>SAND PAD SIZES (Included)</b>	76.2 mm / 114.3 mm / 139.7 mm
<b>MAX FREE SPEED</b>	18,000 RPM
<b>SPINDLE THREAD SIZE</b>	11 mm – 20 UNF
<b>OPERATING AIR PRESSURE</b>	90 PSI
<b>AV. AIR CONSUMPTION</b>	8 CFM
<b>RECOMMENDED HOSE SIZE</b>	3/8" ID
<b>AIR INLET SIZE</b>	1/4" BSP
<b>LENGTH</b>	114 mm
<b>WEIGHT</b>	1.06 KG
<b>ORDER NO.</b>	<b>53-AT-600US</b>
<b>QUICK CHANGE ADAPTOR</b>	<b>SPL-1 SPL-2 SPL-3 AT-600Q*</b>



## VERTICAL SANDER & POLISHER

53-AT-788V & 53-AT-788VP

	<b>SANDER</b>	<b>POLISHER</b>
<b>BACKING PAD SIZES</b>	171 mm	171 mm
<b>MAX FREE SPEED</b>	4500 RPM	2300 RPM
<b>SPINDLE THREAD SIZE</b>	5/8 – 11 UNF	5/8 – 11 UNF
<b>OPERATING AIR PRESSURE</b>	90 PSI	90 PSI
<b>AV. AIR CONSUMPTION</b>	6 CFM	6 CFM
<b>RECOMMENDED HOSE SIZE</b>	3/8" ID	3/8" ID
<b>AIR INLET SIZE</b>	1/4" BSP	1/4" BSP
<b>LENGTH</b>	190 mm	190 mm
<b>WEIGHT</b>	2.6 KG	2.6 KG
<b>ORDER NO.</b>	<b>53-AT-788V</b>	<b>53-AT-788VP</b>
<b>SUPER BUFF ADAPTOR (POLISHER)</b>		<b>17-173895</b>
<b>WOOL SUPER BUFF PAD (POLISHER)</b>		<b>17-233804</b>

